

3.Specification Tables

94L/98/98T

(3-1) Rated Output Table (STANDARD NET)

Model			4TNV94L	4TNV98	4TNV98T
Combustion type			DI (Direct injection)		
Aspiration			N/A	N/A	T/C
Number of cylinders — Bore × Stroke (mm × mm)			4 — 94 × 110	4 — 98 × 110	4 — 98 × 110
Displacement (cc)			3053	3318	3318
Revolution speed (min ⁻¹)			Output Net power kW (PS) [GROSS POWER kW]		
Industrial use	Rated Output	2000	35.3 (48.0) [35.9]	41.9 (57.0) [42.5]	50.7 (69.0) [51.6]
		2200	38.2 (52.0) [39.0]	45.6 (62.0) [46.3]	55.5 (75.5) [56.6]
		2400	41.6 (56.5) [42.4]	49.3 (67.0) [50.2]	60.3 (82.0) [61.8]
		2500	43.0 (58.5) [44.0]	51.1 (69.5) [52.1]	62.5 (85.0) [64.1]
		2600	—	—	—
		2800	—	—	—
		3000	—	—	—
		3200	—	—	—
		3400	—	—	—
		3600	—	—	—
Generator use	Rated Output	1500	29.1 (39.5) [29.3]	34.6 (47.0) [34.9]	41.9 (57.0) [42.3]
		1800	34.6 (47.0) [35.0]	41.2 (56.0) [41.6]	50.4 (68.5) [51.0]
		3000	—	—	—
		3600	—	—	—
	Cont. Rating	1500	26.1 (35.5) [26.4]	30.9 (42.0) [31.2]	37.9 (51.5) [38.2]
		1800	31.3 (42.5) [31.7]	36.8 (50.0) [37.2]	45.6 (62.0) [46.2]
		3000	—	—	—
		3600	—	—	—