Safety Data Sheet



SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

YANMAR Genuine Diesel Engine Oil - SAE 15W-40

Product Number(s): 15W40-1L, 15W40-5L, 15W40-20L, 15W40-208L

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Diesel Engine Oil

1.3 Details of the supplier of the safety data sheet

YANMAR Europe BV Brugplein 11 1332 BS ALMERE The Netherlands

email: parts.costatus-yeu@yanmar.com

1.4 Emergency telephone number

Transportation Emergency Response

Europe: 0044/(0)18 65 407333 (English only)

Health Emergency

Europe: 0044/(0)18 65 407333 (English only)

Poison Control Center: Belgium: 0032/(0)70 245 245

Product Information

Product Information: FAX number: 0032/(0)9 293 72 22

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLP CLASSIFICATION: Not classified as dangerous according to EU regulatory guidelines.

2.2 Label elements

Under the criteria of Regulation (EC) No 1272/2008 (CLP): Not classified

voi ciassilled

- contains: Benzenesulfonic acid, methyl-, mono-C20-26-branched alkyl derivs.,

calcium salts. May produce an allergic reaction.

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs.,

calcium salts.

May produce an allergic reaction.

2.3 Other hazards Not Applicable

Revision number: 4 1 of 12 Yanmar Genuine Diesel Engine Oil
Revision date: MAY 6, 2020 SAE 15W40

MSDS: 32556

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS NUMBER	EC NUMBER	REGISTRATION NUMBER	CLP CLASSIFICATION	AMOUNT
Highly refined mineral oil (C15 - C50)	Mixture	*	***	None	70 - 99 %weight
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	68784-31-6	272-238-5	01-2119657973-23	Aquatic Chronic 2/H411; Eye Dam. 1/H318	1 - < 2.5% weight
Benzenesulfonic acid, methyl-, mono-C20-26- branched alkyl derivs., calcium salts	722503-69-7	Not applicable	**	Skin Sens. 1B/H317	< 1 %weight
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	722503-68-6	Not applicable	**	Skin Sens. 1B/H317	0.1 - < 1 %weight

The full text of all CLP H-statements is shown in Section 16.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs. If exposure to hydrogen sulfide (H2S) gas is possible during an emergency, wear an approved, positive pressure air-supplying respirator. Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Revision number: 4 2 of 12 Yanmar Genuine Diesel Engine Oil
Revision date: MAY 6, 2020 SAE 15W40

MSDS: 32556

^{*}Contains one or more of the following EINECS numbers: 265-090-8, 265-091-3, 265-096-0, 265-097-6, 265-098-1, 265-101-6, 265-155-0, 265-156-6, 265-157-1, 265-158-7, 265-159-2, 265-160-8, 265-166-0, 265-169-7, 265-176-5, 276-736-3, 276-737-9, 276-738-4, 278-012-2.

^{**}Not available or substance is not currently required for registration under REACH.

^{***} Contains one or more of the following REACH registration numbers: 01-2119488706-23, 01-2119487067-30, 01-2119487081-40, 01-2119483621-38, 01-2119480374-36, 01-2119488707-21,

 $^{01-2119467170-45,\, 01-2119480375-34,\, 01-2119484627-25,\, 01-2119480132-48,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-2119487077-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,\, 01-211948707-29,}$

^{01-2119489287-22, 01-2119480472-38, 01-2119471299-27, 01-2119485040-48, 01-2119555262-43,}

^{01-2119495601-36, 01-2119474889-13, 01-2119474878-16.}

4.2 Most important symptoms and effects, both acute and delayed IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Contact with the skin is not expected to be harmful.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Not expected to be harmful if inhaled. Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty breathing. Hydrogen sulfide has a strong rotten-egg odor. However, with continued exposure and at high levels, H2S may deaden a person's sense of smell. If the rotten egg odor is no longer noticeable, it may not necessarily mean that exposure has stopped. At low levels, hydrogen sulfide causes irritation of the eyes, nose, and throat. Moderate levels can cause headache, dizziness, nausea, and vomiting, as well as coughing and difficulty breathing. Higher levels can cause shock, convulsions, coma, and death. After a serious exposure, symptoms usually begin immediately.

DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS: Not classified.

4.3 Indication of any immediate medical attention and special treatment needed

Note to Physicians: Administration of 100% oxygen and supportive care is the preferred treatment for poisoning by hydrogen sulfide gas. For additional information on H2S, see Chevron MSDS No. 301.

SECTION 5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

5.2 Special hazards arising from the substance or mixture

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of: Calcium, Nitrogen, Zinc, Phosphorus, Sulfur.

5.3 Advice for firefighters

This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition in vicinity of spilled material. Refer to Sections 5 and 8 for more information.

6.2 Environmental precautions

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

Revision number: 4 3 of 12 Yanmar Genuine Diesel Engine Oil

6.4 Reference to other sections

See sections 8 and 13.

SECTION 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not breathe gas. Wash thoroughly after handling.

Unusual Handling Hazards: Toxic quantities of hydrogen sulfide (H2S) may be present in storage tanks and bulk transport vessels which contain or have contained this material. Persons opening or entering these compartments should first determine if H2S is present. See Exposure Controls/Personal Protection -Section 8. Do not attempt rescue of a person over exposed to H2S without wearing approved suppliedair or self-contained breathing equipment. If there is a potential for exceeding one-half the occupational exposure standard, monitoring of hydrogen sulfide levels is required. Since the sense of smell cannot be relied upon to detect the presence of H2S, the concentration should be measured by the use of fixed or portable devices.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/ or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

7.2 Conditions for safe storage, including any incompatibilities Not Applicable

7.3 Specific end use(s): Diesel Engine Oil

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

8.1 Control parameters

Revision date: MAY 6, 2020

Occupational Exposure Limits:

Component	Country/ Agency	Form	TWA	STEL	Ceiling	Notation
Highly refined mineral oil	Belgium		5 mg/m3	10 mg/m3	-	

Revision number: 4 Yanmar Genuine Diesel Engine Oil 4 of 12

> **SAE 15W40** MSDS: 32556

(C15 - C50)

Consult local authorities for appropriate values.

8.2 Exposure controls **ENGINEERING CONTROLS:**

Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: No special protective clothing is normally required. Where splashing is possible, select protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: 4H (PE/EVAL). Nitrile Rubber, Silver Shield, Viton,

Respiratory Protection: No respiratory protection is normally required. If material is heated and emits hydrogen sulfide, determine if airborne concentrations are below the occupational exposure limit for hydrogen sulfide. If not, wear an approved positive pressure air-supplying respirator. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge.

ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

9.1 Information on basic physical and chemical properties

Appearance

Color: Light to Brown Physical State: Liquid Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Melting Point: No data available Freezing Point: Not Applicable

Initial Boiling Point: No data available

Flashpoint: (Cleveland Open Cup) 215 °C (419 °F) (Minimum)

Evaporation Rate: No data available Flammability (solid, gas): Not Applicable

Flammability (Explosive) Limits (% by volume in air):

Lower: Not Applicable Upper: Not Applicable

Vapor Pressure: No data available

Vapor Density (Air = 1): No data available **Density:** 0.8799 kg/l @ 15°C (59°F) (Typical)

Solubility: Soluble in hydrocarbons; insoluble in water Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: No data available **Decomposition temperature:** No data available Viscosity: 111.20 mm2/s @ 40°C (104°F) (Typical)

Explosive Properties: No Data Available Oxidising properties: No Data Available

Revision number: 4 Yanmar Genuine Diesel Engine Oil 5 of 12

9.2 Other Information: No Data Available

SECTION 10 STABILITY AND REACTIVITY

10.1 Reactivity: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.2 Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.

10.4 Conditions to Avoid: Not applicable

10.5 Incompatible materials to avoid: Not applicable

10.6 Hazardous decomposition products: Alkyl Mercaptans (Elevated temperatures), Hydrogen

Sulfide (Elevated temperatures)

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product Information:

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (dermal): Not Applicable

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (oral): Not Applicable

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (inhalation): Not Applicable

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Single Exposure: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Repeated Exposure: The hazard evaluation is based on data for components or a similar material.

Aspiration Hazard: No data available

Component Information:

Serious Eye Damage/Irritation:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Test Result: Causes serious eye damage * read-across data from similar material
Benzenesulfonic acid, methyl-, mono-C20-26-	Based on available data, the classification criteria are not met

Revision number: 4 6 of 12 Yanmar Genuine Diesel Engine Oil

branched alkyl derivs., calcium salts	
Benzenesulfonic acid, methyl-, mono-	Based on available data, the classification criteria are not met
C20-24-branched alkyl derivs., calcium salts	

Skin Corrosion/Irritation:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec- Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Skin Sensitization:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met	
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Test Result: May cause allergic skin reaction * read-across data from similar material	
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Test Result: May cause allergic skin reaction * read-across data from similar material	

Acute Dermal Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Acute Oral Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Acute Inhalation Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Germ Cell Mutagenicity:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phosphorodithioic acid, mixed O,O-bis(sec- Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met	
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met	
Benzenesulfonic acid, methyl-, mono-C20-24-	Based on available data, the classification criteria are not met	

Revision number: 4 7 of 12 Yanmar Genuine Diesel Engine Oil
Revision date: MAY 6, 2020 SAE 15W40

SAE 15W40 MSDS: 32556

branched alkyl derivs., calcium salts	

Carcinogenicity:		
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met	
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met	
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met	
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met	

Reproductive Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Specific Target Organ Toxicity - Single Ex	posure:
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Specific Target Organ Toxicity - Repeated	Exposure:
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

ADDITIONAL TOXICOLOGY INFORMATION:

In accordance with the Directive 94/69/EC (21st ATP to DSD), Nota L, reference IP 346/92: "DMSO Extraction Method", we have determined that the base oils used in this preparation are not carcinogenic. During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

SECTION 12 ECOLOGICAL INFORMATION

Product Information:

12.1 Toxicity

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Revision number: 4 Yanmar Genuine Diesel Engine Oil 8 of 12

Revision date: MAY 6, 2020

12.2 Persistence and degradability

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Octanol/Water Partition Coefficient: No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

12.6 Other adverse effects

No other adverse effects identified.

Component Information:

Acute Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O- bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	Test Qualifier: EC50 Test Result: 1.2 mg/l Species: Invertebrate Duration:48 hour(s) * read-across data from similar material
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Long-term Toxicity:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec- Bu and 1,3-dimethylbutyl) esters, zinc salts	No test data available
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Biodegradation:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec- Bu and 1,3-dimethylbutyl) esters, zinc salts	Test Result: Not readily biodegradable
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono- C20-24-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met

Bioaccumulative Potential:	
Highly refined mineral oil (C15 - C50)	Based on available data, the classification criteria are not met
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	No test data available
Benzenesulfonic acid, methyl-, mono- C20-26-branched alkyl derivs., calcium salts	Based on available data, the classification criteria are not met
Benzenesulfonic acid, methyl-, mono-C20-	Based on available data, the classification criteria are not met

Revision number: 4 9 of 12 Yanmar Genuine Diesel Engine Oil

24-branched alkyl derivs., calcium salts

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

In accordance with European Waste Catalogue (E.W.C.) the codification is the following: 13 02 05

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

ADR/RID

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable **14.3 Transport hazard class(es):** Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

ICAO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable **14.3 Transport hazard class(es):** Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

IMO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable **14.3 Transport hazard class(es):** Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REGULATORY LISTS SEARCHED:

01=EU Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.

Revision number: 4 10 of 12 Yanmar Genuine Diesel Engine Oil

```
02=EU Directive 90/394/EEC: Carcinogens at work.
```

No components of this material were found on the regulatory lists above.

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), ENCS (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

One or more components is listed on ELINCS (European Union). All other components are listed or exempted from listing on EINECS.

15.2 Chemical safety assessment

No chemical safety assessment.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: SECTION 01 - Company MSDS Address information was

modified. SECTION 01 - Health Emergency information was modified.

SECTION 01 - Identified Uses information was modified.

SECTION 03 - Composition information was modified.

SECTION 04 - First Aid - Inhalation information was modified.

SECTION 04 - First Aid - Note to Physicians information was added.

SECTION 04 - Immediate Health Effects - Inhalation information was modified.

SECTION 07 - Identified Uses information was modified.

SECTION 07 - Precautionary Measures information was modified.

SECTION 07 - Unusual Handling Hazards information was added.

SECTION 08 - Occupational Exposure Limit Table information was modified.

SECTION 08 - Respiratory Protection information was modified.

SECTION 09 - Physical/Chemical Properties information was deleted.

SECTION 09 - Physical/Chemical Properties information was modified.

SECTION 11 - Toxicological Information information was added.

SECTION 12 - Ecological Information information was added.

SECTION 16 - Full Text of H-Statements information was modified.

Revision Date: May 06, 2020

Full text of CLP H-statements:

H411; Toxic to aquatic life with long lasting effects

H318; Causes serious eye damage

H317; May cause allergic skin

reaction

Revision number: 4 11 of 12 Yanmar Genuine Diesel Engine Oil

Revision date: MAY 6, 2020

MSDS: 32556

⁰³⁼EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

⁰⁴⁼EU Directive 96/82/EC (Seveso II): Article 9.

⁰⁵⁼EU Directive 96/82/EC (Seveso II): Articles 6 and 7.

⁰⁶⁼EU Directive 98/24/EC: Chemical agents at work.

⁰⁷⁼EU Directive 2004/37/EC: On the protection of workers.

⁰⁸⁼EU Regulation EC No. 689/2008: Annex 1, Part 1.

⁰⁹⁼EU Regulation EC No. 689/2008: Annex 1, Part 2.

¹⁰⁼EU Regulation EC No. 689/2008: Annex 1, Part 3.

¹¹⁼EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).

¹²⁼EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances. mixture & article.

¹³⁼EU REACH, Annex XIV: Candidate List of Substances of Very High Concern for Authorization (SVHC).

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA	-	Time Weighted Average
STEL - Short-term Exposure Limit	PEL	-	Permissible Exposure Limit
CVX - Chevron		-	Chemical Abstract Service Number
NQ - Not Quantifiable			

Prepared according to the EU Regulation 1907/2006 (as amended) by Chevron Energy Technology Company, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

N	ı	Δ	n	n	^	v
- 17	40	^	40	ш	-	

Revision number: 4 12 of 12 Yanmar Genuine Diesel Engine Oil